# INTELLIGENCE

# Freezer/Refrigerator Monitoring System

#### **Features**

- Temperaure (0-50 C.) Humidity (0-100%)
- 1 x 4-20 mA Freezer Room Temperature Output
  - 1 x Form A Alarm Relay Output
- WLAN Built-in
- Send Alarm Messages via LINE/Email Notification
- Built-in Data Logger
- Back Up Rechargable Battary Built-in
- Remote Monitoring Feature via IOT Cloud
- Integrated With All Intelligence Field-Controller



Intelligent Control Systems Co., Ltd.

391 Silom Road Bangkok 10500 Thailand

Tel: (662) 2668852-4 (662) 2665197 Email : info@ics.co.th Website: http://ics.co.th The INTELLIGENCE TH152W is an Stand Alone WiFi Web Server Room Temperature/ Humidity Monitoring and Alarm Module that gives an integrated system solution for monitoring room temperature/humidity in the facility. The module can be integrated with other INTELLIGENCE field modules through TCP/IP Network Protocol for a wide range of facility monitoring/control function, such as; room temperature/humidity monitoring or electrical sub metering through a software configuration.

# **Outputs**

The TH-152W provides one 4-20mA Room Temperature and one alarm relay Outputs which can be used to interface to SCADA system.

### **Alarm Notification**

The TH152W provides a built-in LINE/Email Notification feature to notify the operator In case of the current temperature of the unit rises above or fall below the preset limit, freezer door left to be too long open or power supply failure.

#### **Historical Data Record**

The TH-152W provides a built-in SD card for recording the historical data up to 1 year and the past room temperatures/Humidity with the time and date can be automatically recorded and stored as a files and can be exported in a CSV or Excel format.

# **Cloud Based Real Time Monitoring**

The TH-152W provides the remote monitoring feature that allows the user is able to monitor Real time room temperature/ humidity remotely over the mobile phone through IOT cloud based.

# INTELLIGENCE

# Model TH-152W

WIFI Room Temperature/Humidity Monitoring Unit with 4-20 mA Output



## **Specifications**

Power 5VDC

Back up Battery Rechargeable Litium-

Polymer

Display: OLED 128x64

Real Time Clock: Built-in RTC with back

up battery

Measuring Range: Temperature 0-50 C.

Humidity 0-100%

Outputs: 1 x 4-20mA

Temperature

Output (-200 to 50

Deg.C)

1 x Form A Alarm Relay

**Communications** WLAN

Alarm Notify:

Notification

via LINE/Email

(Built -in)

Data Logger: 1 Year Data Historical

Data Record

Protocol Support: MODBUS TCP

**MQTT**